
nichicon


UCZ

Chip Type, High Reliability.
Low temperature ESR specification.

For SMD | Long Life | Anti-Solvent Feature

- Chip type, high temperature range, for +125°C use.
- Added ESR specification after the test at -40°C.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU).






■Specifications


Item	Performance Characteristics
Category Temperature Range	−40 to +125°C
Rated Voltage Range	10 to 100V
Rated Capacitance Range	10 to 3300μF
Capacitance Tolerance	±20% at 120Hz, 20°C
Leakage Current	After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01CV or 3μA, whichever is greater.
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C Rated voltage (V): 10 / 16 / 25 / 35 / 50 / 63 / 80 / 100 tan δ (MAX.): 0.30 / 0.23 / 0.18 / 0.16 / 0.16 / 0.12 / 0.12 / 0.10 For capacitance of more than 1000μF, add 0.02 for every increase of 1000μF.
Stability at Low Temperature	Rated voltage (V): 10 / 16 / 25 / 35 / 50 / 63 / 80 / 100 Impedance ratio ZT / Z20 (MAX.) Z−40°C / Z+20°C: 12 / 8 / 6 / 4 / 4 / 3 / 3 / 3 Measurement frequency : 120Hz
Endurance	After continuous application of rated voltage at 125°C and then restoring down to 20°C, the readings of measurements shall meet below. Case size: φ6.3 × 5.8L / φ6.3 × 7.7L / φ8 to φ12.5 / φ16,18 × 16.5L / φ16,18 × 21.5L Endurance time: 1000hrs. / 2000hrs. / 3000hrs. / 3500hrs. / 4000hrs. Capacitance change: Within ±30% of the initial capacitance value tan δ: 300% or less than the initial specified value Leakage current: Less than or equal to the initial specified value
Shelf Life	After storing the capacitors under no load at 125°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C. Capacitance change: Within ±10% of the initial capacitance value tan δ: Less than or equal to the initial specified value Leakage current: Less than or equal to the initial specified value
Marking	Black print on the case top.

■Chip Type


(φ 6.3)【Standard】※ φ6.3 × 5.8L : The vibration structure-resistant product can't support.
φ6.3 × 7.7L : The vibration structure-resistant product is available.



(φ 8 , φ10) 【Standard】



(φ12.5 to φ18)【Standard】



※φ12.5 to φ18 :
The vibration structure-resistant product is also available upon request, please ask for details.

Type numbering system (Example : 35V 47μF)


1	2	3	4	5	6	7	8	9	10	11	12	13	14
U	C	Z	1	V	4	7	0	M	C	L	1	G	S

Package code
Size code
Configuration
Capacitance tolerance (±20%)
Rated capacitance (47μF)
Rated voltage (35V)
Series name
Type

Size	Package	Code
φ4 to 10	Taping	GS
φ12.5 to 18	Taping	MS
φ12.5 to 18	Tray	ZD

φD	Configuration	Code
6.3 to 10	Standard	CL
	Vibration Resistance	CS
12.5 or more	Standard	NQ

(φ 8 , φ10) 【Vibration Resistance】



Standard (mm)

φDXL	6.3X5.8	6.3X7.7	8X10	10X10	12.5X13.5	16X16.5	16X21.5	18X16.5	18X21.5
A	2.4	2.4	2.9	3.2	4.8	5.4	5.4	6.4	6.4
B	6.6	6.6	8.3	10.3	13.6	17.1	17.1	19.1	19.1
C	6.6	6.6	8.3	10.3	13.6	17.1	17.1	19.1	19.1
E	2.2	2.2	3.1	4.5	4	6.3	6.3	6.3	6.3
L	5.8	7.7	10	10	13.5	16.5	21.5	16.5	21.5
H	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4	1.0 to 1.4

Vibration Resistance (mm)

φDXL	8X10	10X10
A	2.9	3.2
B	8.3	10.3
C	8.3	10.3
E	3.1	4.5
L	10	10
H	1.1 to 1.5	1.1 to 1.5

Voltage

V	10	16	25	35	50	63	80	100
Code	A	C	E	V	H	J	K	2A

UCZ

■Dimensions

Cap. (μF) \ V / Code	10 / 1A	16 / 1C	25 / 1E	35 / 1V	50 / 1H
10 / 100				6.3 x 5.8 1.60 24 – 69	6.3 x 5.8 2.80 42 – 51
22 / 220				6.3 x 5.8 1.60 24 – 69	6.3 x 7.7 0.50 5 40 197
33 / 330			6.3 x 5.8 1.60 24 – 69	6.3 x 7.7 0.45 5 40 197	●6.3 x 7.7 0.50 5 40 197 8 x 10 0.25 3.5 6 270
47 / 470		6.3 x 5.8 1.60 24 – 69	Recommend 35V ⇨	●6.3 x 7.7 0.45 5 40 197 8 x 10 0.20 3 4.5 270	●6.3 x 7.7 0.50 5 40 197 8 x 10 0.25 3.5 6 270
68 / 680				8 x 10 0.20 3 4.5 270	
100 / 101	Recommend 16V ⇨	●6.3 x 7.7 0.45 5 40 197 8 x 10 0.20 3 4.5 270	●6.3 x 7.7 0.45 5 40 197 8 x 10 0.20 3 4.5 270	8 x 10 0.20 3 4.5 270	10 x 10 0.20 2.5 4.5 500
220 / 221	8 x 10 0.20 3 4.5 270	8 x 10 0.20 3 4.5 270	●8 x 10 0.20 3 4.5 270 10 x 10 0.15 2 3.5 500	10 x 10 0.15 2 3.5 500	
330 / 331	●8 x 10 0.20 3 4.5 270 10 x 10 0.15 2 3.5 500	10 x 10 0.15 2 3.5 500	10 x 10 0.15 2 3.5 500		
390 / 391					12.5 x 13.5 0.100 0.44 4.0 1300
470 / 471	10 x 10 0.15 2 3.5 500	10 x 10 0.15 2 3.5 500		12.5 x 13.5 0.060 0.40 3.0 1700	16 x 16.5 0.080 0.34 2.6 2000
560 / 561				12.5 x 13.5 0.060 0.40 3.0 1700	16 x 16.5 0.080 0.34 2.6 2000
680 / 681				12.5 x 13.5 0.060 0.40 3.0 1700	18 x 16.5 0.078 0.32 2.6 2100
820 / 821			12.5 x 13.5 0.060 0.40 3.0 1700	16 x 16.5 0.047 0.28 1.4 2400	18 x 16.5 0.078 0.32 2.6 2100
1000 / 102			12.5 x 13.5 0.060 0.40 3.0 1700	16 x 16.5 0.047 0.28 1.4 2400	16 x 21.5 0.040 0.22 1.5 2800
1200 / 122			16 x 16.5 0.047 0.28 1.4 1700	18 x 16.5 0.045 0.28 1.4 2600	18 x 21.5 0.038 0.20 1.5 2900
1400 / 142				18 x 16.5 0.045 0.28 1.4 2600	
1600 / 162			16 x 16.5 0.047 0.28 1.4 2400	16 x 21.5 0.034 0.20 0.6 3000	
2200 / 222			18 x 16.5 0.045 0.23 1.3 2600	18 x 21.5 0.032 0.16 0.5 3250	Case size φD x L (mm) / Initial 20°C / Initial -40°C / after endurance test -40°C※ / Rated ripple ESR(100kHz)
2700 / 272			16 x 21.5 0.034 0.20 0.6 3000		
3300 / 332			18 x 21.5 0.032 0.16 0.5 3250		

Cap. (μF) \ V / Code	63 / 1J	80 / 1K	100 / 2A
10 / 100	6.3 x 7.7 2.00 100 – 60	8 x 10 0.75 50 – 70	8 x 10 0.75 50 – 70
22 / 220	8 x 10 0.70 35 – 100	●8 x 10 0.75 50 – 70 10 x 10 0.55 35 – 115	●8 x 10 0.75 50 – 70 10 x 10 0.55 35 – 115
33 / 330	●8 x 10 0.70 35 – 100 10 x 10 0.50 25 – 170	●8 x 10 0.75 50 – 70 10 x 10 0.55 35 – 115	10 x 10 0.55 35 – 115
47 / 470	●8 x 10 0.70 35 – 100 10 x 10 0.50 25 – 170	10 x 10 0.55 35 – 115	
82 / 820			12.5x13.5 0.28 1.9 22 700
150 / 151	12.5 x 13.5 0.20 1.3 14 1000	12.5 x 13.5 0.28 1.9 14 700	16x16.5 0.19 1.4 4.8 1000
180 / 181	12.5 x 13.5 0.20 1.3 14 1000		18x16.5 0.17 1.1 3.9 1100
220 / 221	12.5 x 13.5 0.20 1.3 14 1000		16x21.5 0.12 0.8 2.6 1600
270 / 271		16 x 16.5 0.19 1.4 4.8 1000	
300 / 301			18x21.5 0.11 0.7 2.4 1700
330 / 331		18 x 16.5 0.17 1.1 3.9 1100	
390 / 391	16 x 16.5 0.13 0.9 4.8 1900	16 x 21.5 0.12 0.8 2.6 1600	
470 / 471	18 x 16.5 0.11 0.82 3.9 2000		
520 / 521		18 x 21.5 0.11 0.7 2.4 1700	Case size φD x L (mm) / Initial 20°C / Initial -40°C / after endurance test -40°C※ / Rated ripple ESR(100kHz)
560 / 561	16 x 21.5 0.07 0.46 2.0 2500		
750 / 751	18 x 21.5 0.068 0.44 1.8 2600		

※Guaranteed time of ESR after endurance test

Size	Guaranteed time	
φ6.3 × 5.8L	–	
φ6.3 x 7.7L, φ8 x 10L φ10 x 10L	10 to 50V	2000hrs.
	63 to 100V	–
φ12.5	2000hrs.	
φ16,18 × 16.5L	2000hrs.	
φ16,18 × 21.5L	3000hrs.	

Max. ESR (Ω) at 20°C / -40°C 100kHz, Rated ripple Current (mArms) at 125°C 100kHz

● : In this case, 6 will be put at 12th digit of type numbering system.

● Frequency coefficient of rated ripple current

Frequency	50Hz	120Hz	300Hz	1kHz	10kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

- Taping specifications are given in page 23.
- Recommended land size, soldering by reflow are given in page 18, 19.
- Please refer to page 3 for the minimum order quantity.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Nichicon:

UCZ1A221MCL1GS UCZ1A331MCL1GS UCZ1A331MCL6GS UCZ1A471MCL1GS UCZ1C101MCL1GS
UCZ1C101MCL6GS UCZ1C221MCL1GS UCZ1C331MCL1GS UCZ1C471MCL1GS UCZ1E101MCL1GS
UCZ1E221MCL1GS UCZ1E331MCL1GS UCZ1V101MCL1GS UCZ1V221MCL1GS UCZ1V470MCL1GS
UCZ1V470MCL6GS UCZ1V680MCL1GS UCZ2A220MCS6GS UCZ1A471MCS1GS UCZ1E221MCS6GS
UCZ1E101MCS6GS UCZ1A221MCS1GS UCZ1H470MCS1GS UCZ1J470MCS6GS UCZ1H330MCS6GS
UCZ1V220MCL1GS UCZ1K220MCL1GS UCZ1V100MCL1GS UCZ2A100MCS1GS UCZ1K470MCS1GS
UCZ1J470MCS1GS UCZ2A220MCS1GS UCZ1V101MCS1GS UCZ1J330MCS6GS UCZ1H220MCS1GS
UCZ1H330MCS1GS UCZ1C331MCS1GS UCZ1H101MCS1GS UCZ1H330MCL1GS UCZ1C471MCS1GS
UCZ1K330MCS6GS UCZ1J470MCL1GS UCZ1J330MCL6GS UCZ2A220MCL1GS UCZ1V680MCS1GS
UCZ1K100MCS1GS UCZ1K220MCS1GS UCZ1J100MCL1GS UCZ2A330MCS1GS UCZ1V221MCS1GS
UCZ1E101MCS1GS UCZ1A331MCS6GS UCZ1H470MCL6GS UCZ1C101MCS6GS UCZ1E221MCS1GS
UCZ1E330MCL1GS UCZ1C101MCS1GS UCZ1J220MCL1GS UCZ1H100MCL1GS UCZ1H470MCS6GS
UCZ1K330MCL1GS UCZ1V330MCS1GS UCZ1K220MCL6GS UCZ1K330MCS1GS UCZ1V470MCS6GS
UCZ1V330MCL1GS UCZ1C221MCS1GS UCZ1H101MCL1GS UCZ1E331MCS1GS UCZ1K220MCS6GS
UCZ1J100MCS1GS UCZ1J330MCL1GS UCZ1J220MCS1GS UCZ1H220MCL1GS UCZ1V470MCS1GS
UCZ1K330MCL6GS UCZ1J330MCS1GS UCZ2A100MCL1GS UCZ1C470MCL1GS UCZ1H330MCL6GS
UCZ1A331MCS1GS UCZ1E221MCL6GS UCZ1K100MCL1GS UCZ1K470MCL1GS UCZ1J470MCL6GS
UCZ1H470MCL1GS UCZ2A330MCL1GS UCZ2A220MCL6GS UCZ1E101MCL6GS UCZ1J471MNQ1MS
UCZ1H821MNQ1MS UCZ1K521MNQ1MS UCZ1E821MNQ1MS UCZ1E222MNQ1MS UCZ1K331MNQ1MS
UCZ1J181MNQ1MS UCZ1V681MNQ1MS UCZ1V122MNQ1MS UCZ1V222MNQ1MS UCZ1V471MNQ1MS