

(1,27 mm) .050"

SATA-CM, SATA-SV SERIES

SATA-022-01-L-SV

SATA-022-01-L-CM

SERIAL ATA 22 POSITION

SPECIFICATIONS

For complete specifications see www.samtec.com?SATA-CM

Insulator Material:
Black LCP

Contact Material:
Phosphor Bronze

Operating Temp Range:
-40°C to +105°C

RoHS Compliant:
Yes




SATA

NO. OF
POSITIONS

01

PLATING

CM

-022
(Per Row)-L
= 15μ" (0,38 μm) Gold on post,
Matte Tin on tail-CM
= Cable
Mount

Note: Some lengths, styles and options are non-standard, non-returnable.

SPECIFICATIONS

For complete specifications see www.samtec.com?SATA-SV

Insulator Material:
Black LCP

Terminal Material:
Phosphor Bronze

Contact Material:
Phosphor Bronze

Operating Temp Range:
-40°C to +105°C

RoHS Compliant:
Yes




SATA

NO. OF
POSITIONS

01

PLATING

SV

-022
(Per Row)-L
= 15μ" (0,38 μm) Gold on post,
Matte Tin on tail-SV
= Single
Row,
Vertical
Board
Mount

Note: Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 SAMTEC NORTHERN CALIFORNIA • Tel: 408-395-5900 SAMTEC SOUTHERN CALIFORNIA • Tel: 1-800-726-8329
 SAMTEC AMERICA LATINA COMERCIO EXTERIOR LTDA • Tel: (+55 31) 3786 3227 SAMTEC UNITED KINGDOM • Tel: 44 01236 739292 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 SAMTEC ITALY • Tel: 39 039 6890337 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 SAMTEC BENELUX • Tel: 44 01236 739292
 SAMTEC ISRAEL • Tel: 972-3-7526600 SAMTEC INDIA • Tel: +91-80-3272 1612 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 SAMTEC JAPAN • Tel: 045-475-1385 SAMTEC CHINA • Tel: 86-21-6083 3766
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 SAMTEC HONG KONG • Tel: 852-26904858 SAMTEC KOREA • Tel: 82-31-717-5685 SAMTEC ANZ • Tel: 613 9580 0683