

Item #	Description	1-9	10-24	25-99	100-249	250-499
--------	-------------	-----	-------	-------	---------	---------

DVI Cable Assemblies - Fully Molded with Ferrites

This series of DVI cable assemblies features a molded integrated ferrite on both ends for EMI/RFI protection and a fully molded and shielded backshell. Offered in 4 standard lengths not exceeding the recommended 5 meter maximum for DVI cables.

DVI-I Single Link Cable Assembly with Ferrites

CTLDVI-ISL-MM-3	DVI Cable, DVI-I Single Link Male / Male, 3.0 ft	31.50	29.61	27.72	25.83	23.94
CTLDVI-ISL-MM-5	DVI Cable, DVI-I Single Link Male / Male, 5.0 ft	32.00	30.08	28.16	26.24	24.32
CTLDVI-ISL-MM-10	DVI Cable, DVI-I Single Link Male / Male, 10.0 ft	33.25	31.26	29.26	27.26	25.27
CTLDVI-ISL-MM-15	DVI Cable, DVI-I Single Link Male / Male, 15.0 ft	34.50	32.43	30.36	28.29	26.22

DVI-I Dual Link Cable Assembly with Ferrites

CTLDVI-I-MM-3	DVI Cable, DVI-I Dual Link Male / Male, 3.0 ft	34.75	31.28	27.80	24.33	20.85
CTLDVI-I-MM-5	DVI Cable, DVI-I Dual Link Male / Male, 5.0 ft	35.50	31.95	28.40	24.85	21.30
CTLDVI-I-MM-10	DVI Cable, DVI-I Dual Link Male / Male, 10.0 ft	36.25	32.63	29.00	25.38	21.75
CTLDVI-I-MM-15	DVI Cable, DVI-I Dual Link Male / Male, 15.0 ft	37.00	33.30	29.60	25.90	22.20

DVI-D Single Link Cable Assembly with Ferrites

CTLDVIMM-3	DVI Cable, DVI-D Single Link Male / Male, 3.0 ft	29.50	26.55	23.60	20.65	17.70
CTLDVIMM-5	DVI Cable, DVI-D Single Link Male / Male, 5.0 ft	30.50	27.45	24.40	21.35	18.30
CTLDVIMM-10	DVI Cable, DVI-D Single Link Male / Male, 10.0 ft	33.00	29.70	26.40	23.10	19.80
CTLDVIMM-15	DVI Cable, DVI-D Single Link Male / Male, 15.0 ft	35.50	31.95	28.40	24.85	21.30

DVI-D Dual Link Cable Assembly with Ferrites

CTLDVI-DL-MM-3	DVI Cable, DVI-D Dual Link Male / Male, 3.0 ft	32.75	30.78	28.82	26.85	24.89
CTLDVI-DL-MM-5	DVI Cable, DVI-D Dual Link Male / Male, 5.0 ft	33.50	31.49	29.48	27.47	25.46
CTLDVI-DL-MM-10	DVI Cable, DVI-D Dual Link Male / Male, 10.0 ft	35.50	33.37	31.24	29.11	26.98
CTLDVI-DL-MM-15	DVI Cable, DVI-D Dual Link Male / Male, 15.0 ft	37.50	35.25	33.00	30.75	28.50

DVI Adaptor Cables - Adapt from DVI to HD15 and DFP

This series of cable assemblies allows adaptation from DVI to compatible HD15 and DFP interfaces.

DVI-A to HD15 Cable Assembly with Ferrites

CTLDVI-HD-MM-3	DVI Cable, DVI-A to HD15 Male / Male, 3.0 ft	28.75	25.88	23.00	20.13	17.25
CTLDVI-HD-MM-5	DVI Cable, DVI-A to HD15 Male / Male, 5.0 ft	29.50	26.55	23.60	20.65	17.70
CTLDVI-HD-MM-10	DVI Cable, DVI-A to HD15 Male / Male, 10.0 ft	30.25	27.23	24.20	21.17	18.15
CTLDVI-HD-MM-15	DVI Cable, DVI-A to HD15 Male / Male, 15.0 ft	31.00	27.90	24.80	21.70	18.60

DVI-D to DFP Cable Assembly with Ferrites

CTLDVIMR-3	DVI Cable, DVI-D to DFP Male / Male, 3.0 ft	29.50	26.55	23.60	20.65	17.70
CTLDVIMR-5	DVI Cable, DVI-D to DFP Male / Male, 5.0 ft	30.50	27.45	24.40	21.35	18.30
CTLDVIMR-10	DVI Cable, DVI-D to DFP Male / Male, 10.0 ft	33.00	29.70	26.40	23.10	19.80
CTLDVIMR-15	DVI Cable, DVI-D to DFP Male / Male, 15.0 ft	35.50	31.95	28.40	24.85	21.30

DVI KVM (Keyboard, Video, Mouse) Cables - Mini DIN 6 Connectors

This series of KVM cables is offered in two configurations; one transitioning the video from DVI to HD15 and the second series featuring DVI interfaces on both ends. Both male to male and male to female configurations are available.

DVI / HD15 KVM Cable Assembly Combine DVI-A with HD15 + 2 Mini DIN 6 Connectors

CTLDVIKVM-2	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Male, 2.0m	58.50	54.99	51.48	47.97	44.46
CTLDVIKVM-3	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Male, 3.0m	60.00	56.40	52.80	49.20	45.60
CTLDVIKVM-5	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Male, 5.0m	63.00	59.22	55.44	51.66	47.88
CTLDVIKVMF-2	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Female, 2.0m	59.00	55.46	51.92	48.38	44.84
CTLDVIKVMF-3	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Female, 3.0m	60.50	56.87	53.24	49.61	45.98
CTLDVIKVMF-5	DVI KVM Cable, DVI-A to HD15 + 2 Mini DIN 6 Male / Female, 5.0m	63.50	59.69	55.88	52.07	48.26

DVI KVM Cable Assembly Combine DVI-D + 2 Mini DIN 6 Connectors

CTLKVM-2	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Male, 2.0m	54.50	51.23	47.96	44.69	41.42
CTLKVM-3	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Male, 3.0m	56.00	52.64	49.28	45.92	42.56
CTLKVM-5	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Male, 5.0m	59.00	55.46	51.92	48.38	44.84
CTLKVMF-2	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Female, 2.0m	55.00	51.70	48.40	45.10	41.80
CTLKVMF-3	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Female, 3.0m	56.50	53.11	49.72	46.33	42.94
CTLKVMF-5	DVI KVM Cable, DVI-D + 2 Mini DIN 6 Male / Female, 5.0m	59.50	55.93	52.36	48.79	45.22

HDMI Cable Assemblies - Fully Molded

High Definition Multimedia Interface (HDMI) is the latest interface for the connection of audio/video equipment. HDMI is the first industry supported uncompressed all digital audio/video interface. HDMI is fully backwards compatible with DVI video signals. HDMI simplifies interconnections between the signal generating device and the display device by including both the audio and video digital signal in one interface.

CTLHDMI-MM-1	HDMI Cable, HDMI Male / Male 1.0m	30.00	27.00	24.00	21.00	18.00
CTLHDMI-MM-2	HDMI Cable, HDMI Male / Male 2.0m	35.75	32.18	28.60	25.03	21.45
CTLHDMI-MM-3	HDMI Cable, HDMI Male / Male 3.0m	41.50	37.35	33.20	29.05	24.90
CTLHDMI-MM-4	HDMI Cable, HDMI Male / Male 4.0m	47.25	42.53	37.80	33.07	28.35
CTLHDMI-MM-5	HDMI Cable, HDMI Male / Male 5.0m	53.00	47.70	42.40	37.10	31.80
CTLHDMI-DVI-MM-1	HDMI Cable, HDMI Male / DVI-D Male, Single Link, 1.0m	25.00	22.50	20.00	17.50	15.00
CTLHDMI-DVI-MM-2	HDMI Cable, HDMI Male / DVI-D Male, Single Link, 2.0m	30.75	27.68	24.60	21.53	18.45
CTLHDMI-DVI-MM-3	HDMI Cable, HDMI Male / DVI-D Male, Single Link, 3.0m	36.50	32.85	29.20	25.55	21.90
CTLHDMI-DVI-MM-4	HDMI Cable, HDMI Male / DVI-D Male, Single Link, 4.0m	42.25	38.03	33.80	29.58	25.35
CTLHDMI-DVI-MM-5	HDMI Cable, HDMI Male / DVI-D Male, Single Link, 5.0m	48.00	43.20	38.40	33.60	28.80

**TIP: What is the difference between DVI single link and dual link?**

DVI dual link as the name implies has more conductors than the DVI single link for transmitting signal. Single link DVI supports a maximum bandwidth of 165 MHz (1920 x 1080 at 60 Hz, 1280 x 1024 at 85 Hz) and utilizes 12 of the 24 available pins. Dual link DVI utilizes all 24 available pins and supports 2x 165 MHz maximum bandwidth (2048 x 1536 at 60 Hz, 1920 x 1080 at 85 Hz).

